

Classic Series

**C7 II · 445-465W
MWT Mono PERC Half-Cut Module**

21.0%

Module efficiency up to 21.0%

Features



Innovative Layout

Innovative back contact module layout with asymmetric design for higher efficiency power



High Reliability

Conductive back sheet 2D encapsulation without soldering, resulted lower degradation under multiple extreme testing condition



High ROI

Higher return on investment with higher power output



High Efficiency

MWT back contact cell and modules with busbar-free design and higher efficiency



Superior Warranty

MWT single-glass module with 30-year power warranty by LLOYD'S&PICC worldwide



Lead Free


Eco-friendly PV design achieves Lead-free without soldering materials

Reinsurance Coverage for 30 Years



Insured by PICC and LLOYD'S

PICC LLOYD'S



※1st year degradation less than 2%, 30 years linear power output 82% guaranteed.

Comprehensive Qualifications & Certifications

- ★CQC Top Runner Advanced Technology Certification (4A class)
- ★ISO 9001:2015 Quality Management System
- ★ISO 45001: 2018 Occupation Health Safety Management System

- ★TUV NORD Certification
- ★ISO 14001:2015 Environment Management System



Jiangsu Sunport Power Corp., Ltd

Add: No.20, Xishi Road, Xinwu District, Wuxi, China 214028

Email: info@sunportpower.com

Web: www.sunportpower.com

Electrical Characteristics at Standard Test Conditions(STC)

Spec/Model	Unit	SPP445NHJH	SPP450NHJH	SPP455NHJH	SPP460NHJH	SPP465NHJH
Max-Power(Pm)	W	445	450	455	460	465
Power Tolerance	W			0~+5		
Max-Power Voltage(Vm)	V	43.6	43.8	44.0	44.2	44.4
Max-Power Current(Im)	A	10.22	10.28	10.35	10.42	10.48
Open-Circuit Voltage(Voc)	V	52.7	52.9	53.1	53.3	53.5
Short-Circuit Current(Isc)	A	10.75	10.82	10.89	10.95	11.00
Module Efficiency(ηm)	%	20.1	20.3	20.5	20.8	21.0

STC: AM=1.5, Irradiation 1000W/m², Module Temperature 25°C

Electrical Characteristics at Nominal Module Operating Temperature (NMOT)

Spec/Model	Unit	SPP445NHJH	SPP450NHJH	SPP455NHJH	SPP460NHJH	SPP465NHJH
Max-Power(Pm)	W	334	338	342	346	350
Max-Power Voltage(Vm)	V	41.0	41.2	41.4	41.6	41.8
Max-Power Current(Im)	A	8.15	8.21	8.27	8.32	8.38
Open-Circuit Voltage(Voc)	V	49.7	49.9	50.1	50.3	50.5
Short-Circuit Current(Isc)	A	8.70	8.75	8.80	8.85	8.90

NMOT: Irradiation 800W/m², Ambient temperature 20°C, Wind Speed 1m/s

Temperature Coefficient

Nominal Module Operating Temperature	43±2°C
Temperature coefficient of Pmax	-0.36%/°C
Temperature coefficient of Voc	-0.28%/°C
Temperature coefficient of Isc	0.06%/°C

Package

Transportation	Container Size	Quantity(pcs)	Quantity(per pallet)
Container	40' HC	682	31



Mechanical Characteristics

Dimension(L×W×H)	2005mmx1105mmx35mm
Weight	26kg
Glass Type	High Transmittance Anti-reflective Coated Tempered Glass /3.2mm
Solar Cell	156(12x13) / Mono / 162.75mm (Half-cell)
Encapsulant	EVA
Frame	Anodized Aluminum Alloy / Silver
Junction Box	IP67 / IP68
Cable	4mm ² , 450mm (+)/ 150mm (-); Customizable
Connector	MC4 Compatible

Operating Conditions

Max System Voltage	DC1500V(TUV)
Max Fuse Rated Current	15A
Operating Temperature Range	-40°C~+85°C
Mechanical Load	5400Pa (front) /2400Pa (rear)
Max Allowable Hail Load	φ25mm hail, from 1m of distance at 23 m/s
Application Class	Class A

I-V Curve



Module Size

